

FKM 760-1



BED TYPE MILLING MACHINE

FKM 760-1

SPECIFICATIONS

| | |
|---|-------------------------------------|
| working area | 1220 x 360 mm |
| movement longitudinal X | 650 mm (Automatikbetrieb 600 mm) |
| movement cross Y | 360 mm |
| movement in Z | 400 mm |
| spindle speeds | 94 - 2256 U/min 16 steps |
| tool mounts | ISO 40 (SK 40) |
| quill stroke | 180 mm |
| drilling capacity in steel | max. 50 mm |
| drilling feeds | 0,1/0,15/0,3 mm/U |
| automatic table feeds | 24-720 mm/min (8 steps) |
| distance spindle nose - work table | 120-620 mm |
| size of t-slots | T14 |
| power of engine | 1,5/2,4 KW 400V |
| weight | 1.610,00 kg |
| dimensions | 1730 x 1730 x 2300 mm |

EQUIPMENT

- » gears hardend and ground
- » threading attachment
- » automatic feed X- and Y-axis
- » motorized Z-axis adjustment
- » automatic boring quill feed
- » electrical height adjustment of the milling head
- » central lubrication
- » big control panel
- » cooling device
- » 3-axis digital readout



ACCESSORIES

ISO 40 millingchuck Set , drilling chuck with ISO 40 arbor, cooling device

OPTIONAL ACCESSORY

- » Clamping tool kit T14
- » magnet plates magnet plates 250x600
- » reduction sleeve SK40 to MK3
- » drilling accessories keyless drill chuck B16, 1-13mm
- » drilling accessories keyless drill chuck B18 3-16mm
- ...