

Bohr-/milling machine BKM 7163A

Netto: 21.850,00 €

Result (include USt.): 26.001,50 €

plus Versatdkosten

specifications

drilling capacity in steel	50 mm
threadcutting volume	M 42
movement of X-axis	510 mm
movement of Y-axis	380 mm
height adjustment drilling head	530 mm
spindle speeds 1st gear stage	48 - 310 U/min stepless
spindle speeds 2nd gear stage	310 - 2000 U/min stepless
Working Area	1020 x 380 mm (LxW)
spindle adapter	BT 40
quill stroke	240 mm
automatic feeds	0.08 - 0.50 mm/U (6 steps)
distance spindle nose - column	450 mm
max. distance spindlenose - working	680 mm
table t-slots	3 x T14
power of engine	3,7 KW/400 Volt
weight	1.800,00 kg
dimensions	1700x1520x2680 mm

equipment

- high class Ball leadscrews in all axis
- central lubrication for guide ways and Spindles
- hardened gears in in Oil running
- stepless speed
- adjustable guide ways by Gibs
- automatic tool clamping device
- by us günstig umrüstbar to CNC Kordinatenbohrmaschine
- german final control before shipment to Costumer
- produced according DIN 8605

accessoires

Ball leadscrews in all 3 axis, automatic tool mounts, stepless feeds in X+Y axis, motorized positioning of the drilling headit, 3 axis digital measurement system, cooling device, working lamp, threading attachment, german manual