

# FKM 350-1 PD with SK40



# FKM 350-1 PD with SK40

## SPECIFICATIONS

<b>sizes of worktable</b>	800 x 240 mm
<b>working area</b>	730 x 210 mm
<b>movement longitudinal X</b>	500 mm
<b>movement cross Y</b>	230 mm
<b>height adjustment milling head</b>	350 mm
<b>spindle speeds</b>	75-3200 U/min
<b>tool mounts</b>	ISO 40 / SK 40
<b>quill stroke</b>	130 mm
<b>drilling capacity in steel</b>	40 mm
<b>milling Head swiveling</b>	+90°
<b>distance spindle nose - column</b>	290 mm
<b>distance spindle nose - work table</b>	max 445 mm
<b>size of t-slots</b>	14 mm (M12)
<b>power of engine</b>	1,1/1,5 KW 400 Volt
<b>weight</b>	350,00 kg
<b>dimensions</b>	1020 x 860 x 1150 mm

## EQUIPMENT

- » digital depth indicator
- » adjustable guide ways by Gibs
- » big 12 steps speed range of 75 - 3200 U/min
- » high smooth running by hardened and ground gears in in Oil running forward/backward motor rotation
- » prism guideways in all axis
- » gear head 90° swivel-mounted
- » chip protection with safety circuit



## ACCESSORIES

Cover for Guideway for Y + Z-axis, ISO 40 drill chuck arbor, drill chuck, digital depth indicator, threading attachment, Stop block for 90° Position of the milling head, Handwheels Full Metal, working lamp 24V, 3 axis DRO ready mounted