KAMI WERKZEUGMASCHINEN | BOHR- / MILLING MACHINE

# FKM 350-1 PD with SK40

KAMI GmbH - Eisenstraße 20 - 30916 Isernhagen
**Telefon (+49) 511 - 519 312-0**
www.kami-maschinen.de

**BOHR- / MILLING MACHINE**

# FKM 350-1 PD with SK40

## SPECIFICATIONS

| | |
|---|---|
| **sizes of worktable** | 800 x 240 mm |
| **working area** | 730 x 210 mm |
| **movement longitudinal X** | 500 mm |
| **movement cross Y** | 230 mm |
| **height adjustment milling head** | 350 mm |
| **spindle speeds** | 75-3200 U/min |
| **tool mounts** | ISO 40 / SK 40 |
| **quill stroke** | 130 mm |
| **drilling capacity in steel** | 40 mm |
| **milling Head swiveling** | +-90° |
| **distance spindle nose - column** | 290 mm |
| **distance spindle nose - work table** | max 445 mm |
| **size of t-slots** | 14 mm (M12) |
| **power of engine** | 1,1/1,5 KW 400 Volt |
| **weight** | 350,00 kg |
| **dimensions** | 1020 x 860 x 1150 mm |

## EQUIPMENT

- » digital depth indicator
- » adjustable guide ways by Gibs
- » big 12 steps speed range of 75 - 3200 U/min
- » high smooth running by hardened and ground gears in in Oil running forward/backward motor rotation
- » prism guideways in all axis
- » gear head 90° swivel-mounted
- » chip protection with safety circuit

## ACCESSOIRIES

Cover for Guideway for Y + Z-axis, ISO 40 drill chuck arbor,
drill chuck, digital depth indicator,
threading attachment, Stop block for 90° Position of the
milling head, Handwheels Full Metal, working lamp 24V,
3 axis DRO ready mounted