

FKM 350 PD



FKM 350 PD

SPECIFICATIONS

sizes of worktable	800 x 240 mm
working area	730 x 210 mm
movement longitudinal X	500 mm
movement cross Y	230 mm
height adjustment milling head	350 mm
spindle speeds	75-3200 U/min
tool mounts	ISO 30 / SK 30
quill stroke	130 mm
drilling capacity in steel	40 mm
milling Head swiveling	+ -90°
distance spindle nose - column	290 mm
distance spindle nose - work table	max 445 mm
Machine height with raised milling head max.	1450 mm
size of t-slots	14 mm (M12)
power of engine	1,1/1,5 KW 400 Volt
weight	350,00 kg
dimensions	1020 x 860 x 1150 mm

EQUIPMENT

- » digital depth indicator
- » adjustable guide ways by Gibs
- » big 12 steps speed range of 75 - 3200 U/min
- » high smooth running by hardened and ground gears in in Oil running forward/backward motor rotation
- » prism guideways in all axis
- » gear head 90° swivel-mounted
- » chip protection with safety circuit



ACCESSORIES

Cover for Guideway for Y + Z-axis, ISO 30 drill chuck adapter, drill chuck, digital depth indicator, Taping, Stop block for 90° Position of the milling head, Handwheels Full Metal,

OPTIONAL ACCESSORY

- » other tools cooling device K45
- » Clamping tool kit T14
- » collet chuck set ISO30 ER 32
- » digital readout universal 3 - axis digital readout Brand KAMI (milling machine)
- » Combi milling arbor ISO30 D-22 mm
- ...