

# FKM 350 PVD Super



# FKM 350 PVD Super

## SPECIFICATIONS

<b>table size</b>	800 x 240 mm
<b>movement longitudinal X</b>	520 mm
<b>movement cross Y</b>	205 mm
<b>height adjustment milling head</b>	395 mm
<b>spindle speeds</b>	80 - 3200 U/min stepless in 2 steps
<b>1st switching stage</b>	80 - 980 /min
<b>2nd switching stage</b>	1000 - 3200 U/min
<b>tool mounts</b>	ISO 40 / SK 40
<b>quill stroke</b>	130 mm
<b>drilling capacity in steel</b>	40 mm
<b>distance spindle nose - column</b>	290 mm
<b>distance spindle nose - work table</b>	max 445 mm
<b>size of t-slots</b>	14 mm (M12)
<b>power of engine</b>	2,2 KW 400 Volt
<b>weight</b>	320,00 kg
<b>dimensions</b>	1020 x 860 x 1150 mm

## EQUIPMENT

- » stepless adjustable speed with 2 steps for optimal power transmission
- » digital speed indicator
- » digital depth measuring device
- » adjustable guide ways by Gibs
- » big 2 steps speed range of 75 - 3200 U/min
- » high smooth running by hardened and ground gears in Oil running forward/backward motor rotation
- » Transmission ventilation
- » prism guideways in all axis



## ACCESSORIES

Cover for Guideway for Y - Z-axis, ISO 40 drill chuck arbor, drill chuck, 3-axis digital measurement system ready mounted, stepless speed, Taping, digital depth indicator, X-axis feed and Z-Axis rapid feed move up/down milling Head automatic, central lubrication, Stop block for 90° Position of the milling head, Handwheels Full Metal, working lamp 24V deutschsprachige Operating documents, CE Explaniment