KAMI WERKZEUGMASCHINEN | BOHR- / MILLING MACHINE

FKM 350 PVD Super

KAMI GmbH - Eisenstraße 20 - 30916 Isernhagen
Telefon (+49) 511 - 519 312-0
www.kami-maschinen.de

BOHR- / MILLING MACHINE

FKM 350 PVD Super

SPECIFICATIONS

table size	800 x 240 mm
movement longitudinal X	520 mm
movement cross Y	205 mm
height adjustment milling head	395 mm
spindle speeds	80 - 3200 U/min stepless in 2 steps
1st switching stage	80 - 980 /min
2nd switching stage	1000 - 3200 U/min
tool mounts	ISO 40 / SK 40
quill stroke	130 mm
drilling capacity in steel	40 mm
distance spindle nose - column	290 mm
distance spindle nose - work table	max 445 mm
size of t-slots	14 mm (M12)
power of engine	2,2 KW 400 Volt
weight	320,00 kg
dimensions	1020 x 860 x 1150 mm

EQUIPMENT

- » stepslos adjustable speed with 2 steps for optimal power transmission
- » digital speed indicator
- » digital depth measuring device
- » adjustable guide ways by Gibs
- » big 2 steps speed range of 75 - 3200 U/min
- » high smooth running by hardened and ground gears in in Oil running forward/backward motor rotation
- » Transmission ventilation
- » prism guideways in all axis

ACCESSOIRIES

Cover for Guideway for Y - Z-axis, ISO 40 drill chuck arbor,
drill chuck, 3-axis digital measurement system ready
mounted, stepless speed, Taping,
digital depth indicator, X-axis feed and Z-Axis rapid feed move up/down milling Head
automatic, central lubrication,
Stop block for 90° Position of the milling head,
Handwheels Full Metal,
working lamp 24V
deutschsprachige Operating documents, CE Explainment