

FKM 350 PD with Lackschathe to Special Price

FKM 350 PD with Lackschathe to Special Price

SPECIFICATIONS

sizes of worktable	800 x 240 mm
working area	730 x 210 mm
movement longitudinal X	500 mm
movement cross Y	230 mm
height adjustment milling head	350 mm
spindle speeds	75-3200 U/min
tool mounts	SK 40
quill stroke	130 mm
drilling capacity in steel	40 mm
milling Head swiveling	+/-90°
distance spindle nose - column	290 mm
distance spindle nose - work table	max 445 mm
Machine height with raised milling head max.	1450 mm
size of t-slots	14 mm (M12)
power of engine	1,1/1,5 KW 400 Volt
weight	350,00 kg
dimensions	1020 x 860 x 1150 mm

EQUIPMENT

- » digital depth indicator
- » adjustable guide ways by Gibs
- » big 12 steps speed range of 75 - 3200 U/min
- » high smooth running by hardened and ground gears in Oil running forward/backward motor rotation
- » prism guideways in all axis
- » gear head 90° swivel-mounted
- » chip protection with safety circuit

ACCESSOIRES

Cover for Guideway for Y + Z-axis, SK 40 drill chuck adapter,
drill chuck, digital depth indicator,
Taping, Stop block for 90° Position of the
milling head,
Handwheels Full Metal,