CNC Lathe T 60/750

CNC Lathe with 12 fach tool changer and heavilyem Servomotor. The Time of Toolchange liegt at 0,2s. Mit am Spindledrehmoment of until to 240 Nm. 4-position supported main spindle (2x tworeihigit Cylindrical roller bearing and 2x Angular contact ball bearings) grant a giticherte lifetime of 40.000 operationsstanden.

Price upon inquiry

specifications

max. swing over bed	650 mm
distance between center	760 mm
max.working diameter	380 mm
max. working length	760 mm
spindle bore	76 mm
Bar through	51 mm optional 65 mm
spindlenose	A2-6
speed range build in Motor	1 - 5000 U/min
movement of X-axis	215 mm
movement of Z-axis	832 mm
rapid feed Z-axis	33 m/min
rapidfeed X-Axis	30 m/min
positioning accuracy	0.008 mm
repeat accuracy	0.003 mm
tailstock	programmable
quill diameter	70 mm
quill stroke	80 mm
quill konus	morse cone 4
power of engine permanent	18.5 KW
power of engine short time (30 min)	22.0 KW
weight	5.000,00 kg
dimensions	2955 x 1800 x 1733 mm

accessoiries

hydraulic collet chuck 200 mm, cooling device, programmabler tailstock, 12-fold tool changer, 200 mm hydr. collet chuck, linear guide ways and ball lead screw from THK/Japan, control system Siemens 828D, german Operating documents, CE EC declaration of conformity. To order optionally: conveyor, Workpiece measurement, automatic Toollength correction, Bar feeder, air blow function for tool changer and lathe chuck, cooling by Spindle, high pressure cooling,Oil Mist Collector, 250 mm collet chuck