

T 65/1250



HIGHLIGHTS

- » THK linear guide ways
- » extreme stiffness machinesgittel
- » quickste changing timeen for high Produktivität
- » Randlto the main spindle 0.003 mm
- » positioning accuracy: 0.008 mm
- » Time of Warranty 2 Jahre at aschichtigem operation
- » 6-position supported main spindle
- » also withLive Tools possible to order!

T 65/1250

SPECIFICATIONS

max. swing over bed	650 mm
max. working length	1245 mm
max.working diameter	370 mm
diameter of spindlehole	91 mm
spindle bore/Bar through max.	74 optional 80 mm
spindlenose	A2-8
speed range build in Motor	35 - 4000 U/min
SPindle runout axial	0.003 mm
SPindle runout radial	0.003 mm
tool Stations	12 with cross-section 25 mm
locked of the tool changer	Hydraulic
Time of Toolchange	0.25 s
Toolchange drive by	Servomotor
taper boring tool max.	40 mm
taper Tool cross-section max.	25 mm
movement of X-axis	230 mm
movement of Z-axis	1360 mm
rapid feed Z-axis	33 m/min
rapidfeed X-Axis	30 m/min
positioning accuracy	0.008 mm
repeat accuracy	0.003 mm
quill diameter	100 mm
tailstock + quill stroke	1300 mm
quill konus	morse cone 4
Volumen Hydraulic tank	20 L
Capacity coolant tank max.	190 L
enginepower of cooling pump	550 W
power of engine permanent	22 KW
power of engine short time (30 min)	26 KW
weight	6.000,00 kg
dimensions	3790x2350x1940 mm



ACCESSORIES

cooling device, 12-fold tool changer, 300 mm hydr. collet chuck, linear guide ways and ball lead screw from THK/Japan, control system Siemens 828D, programmabler tailstock, german Operating documents, CE conformityerklärung etc.

Optionen: conveyor, Workpiece measurement, automatic Toollength correction, Bar feeder, air blow function for tool changer and lathe chuck, cooling by Spindle, high pressure cooling, Oil Mist Collector, hollow chuck 250 mm, hydr. Rest SMW Autoblok,