

CNC-Walzendrehmaschine DKM 1250.5 WS-CNC

CNC Walzendrehmaschine for extreme heavy Spataratten best suitable and bitticht by your in hardenn insert erperbte Technik and very stablen bauweise.manualr toolholder for lathe for Sonthewerkzeug cross-section 70X70mm.

Price upon inquiry

specifications

height of center	625 mm
distance between center	5000
bed width	1600 mm
max. swing over bed	1250 mm
guideways	3/4
max. workpiece weight	40 to
diameter of spindlehole	50 mm
speed range	2 - 160 U/min stepless
cutting force max.	130 kN
travel of Top Slider	320 mm
quick feed cross	585 mm/min
rapid feed longitudinal	2000 mm/min
quill diameter	400 mm
travel quill	300 mm
tailstock drive	electrically
power of engine	DC 75 KW
weight	50.000,00 kg

equipment

- bed width 1600 mm
- gears diagonally dovetailed , hardend and ground
- lubrication by integrated pump
- adjustable main spindle bearing
- rapid feed in longitudinal and cross

accessoires

2 piece steady rests, speziell supported Tailstock quill to insert as steady and runninge quill, motorized tailstock to simplen moving by Leverdruck, switch box with aircondition, diagonally dovetailed rack with Reduziergearbox for highest precision and power transmission, Siemens 828, electronical Handle wheel. Optional: Cabin with 2 Movable doors