

3-B precision lathe chuck D=160, cast iron, seperatee jaws



K11
3-jaw self-centering chucks
Solid jaw: Outside jaw & Inside jaw



K12
4-jaw self-centering chucks
Solid jaw: Outside jaw & Inside jaw



K13
6-jaw self-centering chucks
Solid jaw: Outside jaw & Inside jaw



K10-S
2-jaw self-centering chucks
2-pcs jaw : Soft top jaw & Master jaw



K11-A
3-jaw self-centering chucks
2-pcs jaw : Hard top jaw & Master jaw




K12-A
4-jaw self-centering chucks
2-pcs jaw : Hard top jaw & Master jaw



Front mounting type

PLAIN BACK



SIZE D	D1	D2	D3	H1	h	Z-d
80	55	66	16	50	4	3-M6
100	72	84	22	55	4	3-M8
125	95	108	30	58	4	3-M8
130	100	115	30	60	4	3-M8
160	130	142	45	65	5	3-M8
165	130	145	45	65	5	3-M8
180	145	160	50	75	6	3-M10
190	155	172	55	75	6	3-M10
200	165	180	65	75	6	3-M10
230	190	210	70	80	8	3-M12
240	195	215	70	80	8	3-M12
250	206	226	80	80	6	3-M12
315	260	285	100	90	6	3-M16
320	270	290	100	90	6	3-M16
325	272	296	100	90	6	3-M16
380	325	350	130	100	6	3-M16
400	340	368	130	100	6	3-M16
500	440	465	210	115	6	6-M16
630	545	586	252	135	7	6-M16

LATHE CHUCK

3-B precision lathe chuck D=160, cast iron, seperatee jaws

SPECIFICATIONS

D1	130 mm
D2	145 mm
D3	45 mm
H1	65 mm
h	5 mm
Z-d	3-M8
weight	9,00 kg
dimensions	210x210x180 mm

