

SNMG120412E-PC4 AC150P



TURNING INSERT

SNMG120412E-PC4 AC150P

SPECIFICATIONS

Wenof thechneidplattenform	90°
freewinkel	0°
Toleratz	0,127mm
Klemmtyp	G
Schneidelänge	12mm
Plattendicke	4,76mm
Eckenradius	0,8mm
Kattenpräparation	ground Schneide
Spatbrecher	PC4
weight	3,00 kg

BEREICH

Anwendungsbereiche von Wendeschneidplatten zum Drehen

This chart maps various material groups (e.g., 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44, 45, 46, 47, 48, 49, 50, 51, 52, 53, 54, 55, 56, 57, 58, 59, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 82, 83, 84, 85, 86, 87, 88, 89, 90, 91, 92, 93, 94, 95, 96, 97, 98, 99, 100) to specific insert grades (e.g., SNMG120412E-PC4 AC150P) based on their mechanical properties.

BEREICH

Anwendungsbereiche nach Kennzahl

This chart provides a more detailed application guide, mapping specific material grades (e.g., 1000, 1001, 1002, 1003, 1004, 1005, 1006, 1007, 1008, 1009, 1010, 1011, 1012, 1013, 1014, 1015, 1016, 1017, 1018, 1019, 1020, 1021, 1022, 1023, 1024, 1025, 1026, 1027, 1028, 1029, 1030, 1031, 1032, 1033, 1034, 1035, 1036, 1037, 1038, 1039, 1040, 1041, 1042, 1043, 1044, 1045, 1046, 1047, 1048, 1049, 1050, 1051, 1052, 1053, 1054, 1055, 1056, 1057, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1070, 1071, 1072, 1073, 1074, 1075, 1076, 1077, 1078, 1079, 1080, 1081, 1082, 1083, 1084, 1085, 1086, 1087, 1088, 1089, 1090, 1091, 1092, 1093, 1094, 1095, 1096, 1097, 1098, 1099, 1100) to the appropriate insert grade.