KAMI WERKZEUGMASCHINEN | HOLLOW SPINDLEDREHMASCHINE

DKM 1200.2 D460 T

KAMI GmbH - Eisenstraße 20 - 30916 Isernhagen
Telefon (+49) 511 - 519 312-0
www.kami-maschinen.de

HOLLOW SPINDLEDREHMASCHINE

DKM 1200.2 D460 T

SPECIFICATIONS

heigth of center	600 mm
distance between center	2000 mm
diameter of spindlehole	460 mm
max. swing over bed	1200 mm
max. swing over slider	800mm
bed width	755 mm
min. clamping range	500 mm
speed range	forward: (18) 6.3 - 315 U/min
range longitudinal feeds	(56) 0,1 - 12 mm/U
range cross feeds	(56) 0,05 - 6 mm/U
rapid feed longitudinal	1870 mm/min
quick feed cross	935 mm/min
metric thread	(44) 1 - 120 mm
inch thread	(37)30 - 1 1/8 TPI
model thread	(46) 0,5 - 60 mm
diametral pitch	(46) 60 - 0,5 DP
quill diameter	160 mm
power of engine	30 KW
weight	11.000,00 kg
dimensions	5200 x 1980 x 1790 mm

EQUIPMENT

» bed width 755 mm
» automatic feed in longitudinal and cross through one-hand-lever-technic
» rapid feed in longitudinal and cross
» hydraulic clutchs- and Brakesystem
» lubrication by integrated pump
» adjustable main spindle bearing
» overload clutch in apron
» digital readout
» electrically propelled tailstock
» Taper Attachment 300 mm
» short splashguard at Apron or optional full length Splashguard

ACCESSOIRIES

2 x independent chuck 1000 mm

OPTIONAL ACCESSORY

» Quick change tool holder set Gr. D Multifix quick-change steel holder set Gr. D