

## hollow spindledrehmaschine DKM 840.4 T

Heavy Lathe with erwähnenswert big spindle bore of 210 mm.

### Price upon inquiry

#### specifications

height of center	420 mm
distance between center	4000 mm
bed width	550 mm
diameter of spindlehole	210 mm
spindlenose	DIN 55029 C1-15
max. swing over bed	840 mm
max. swing over slider	560 mm
machining length	3850 mm
speed range	45 - 572 U/min; 12 steps
range longitudinal feeds	(32) 0,1 - 1.5 mm/U
range cross feeds	(32) 0,05 - 0.75 mm/U
metric thread	(22) 1 - 15 mm
inch thread	(28) 15 - 1 TPI
modul thread	(21) 0,5 - 7 mm
diametral pitch	(20) 28 - 2 DP
quill diameter	100 mm
quill stroke	300 mm
quill konus	MK 6
power of engine	9/11 KW 2 steps Motor
weight	5.800,00 kg
dimensions	6160x1395x1650 mm

#### equipment

- bed width 550 mm
- automatic feed in longitudinal and cross through one-hand-lever-technic
- rapid feed in longitudinal and cross
- lubrication by integrated pump
- gears diagonally dovetailed , hardend and ground
- multi-plate clutch adjustable
- adjustable main spindle bearing
- overload clutch in apron
- digital readout
- Optional with splash guard

#### accessoires

independent chuck 630 mm, steady and following rest

#### optinalit accessory

Multifix quick-change steel holder set Gr. D

1.098,00 €