

# DKM 1250.1 K



# DKM 1250.1 K

## SPECIFICATIONS

<b>swing over Bed</b>	1250 mm
<b>Workpiece length max</b>	1000 mm
<b>turning diameter toolholder oben</b>	1250 mm
<b>turning diameter toolholder side</b>	1000 mm
<b>max. workpiece weight</b>	3200 Kg
<b>Diameter of Table</b>	1000 mm
<b>speeds</b>	6.3 - 200 U/min (16 steps)
<b>feeds longitudinal/cross</b>	0.8 - 86 mm/min (12 steps)
<b>quick feed cross</b>	1800 mm/min
<b>rapid feed longitudinal</b>	660 mm/min
<b>upper support Z1 axis travel</b>	650 mm
<b>upper support Travel X-Axis1-axis</b>	700 mm
<b>Swiweling of Traverse support</b>	+ - 30°
<b>side support travel Z2-axis</b>	900 mm
<b>side support Travel X-Axis2-axis</b>	630 mm
<b>travel Traverse W-axis</b>	650 mm
<b>rated capacity</b>	22 KW
<b>weight</b>	8.500,00 kg
<b>dimensions</b>	2277x2445x3403 mm

## EQUIPMENT

- » servo drives for all axis
- » digital measurement system for X2-axis
- » central lubrication
- »