

L+Z Lathe DKM 1000 S

Lassen Sie sich durch die Eigenschaften von Kraft, Robustheit und Zuverlässigkeit überzeugen. Mit unseren DKM 1000 und DKM 1250 sind schwere Werkstücke kein Thema mehr. Dank der russischen Bauart, der massiven Konstruktion aller Komponenten und des leistungsstarken 22KW Antriebsmotors, lassen sich mit diesen Maschinenmodellen enorme Spatleistungen erzielen. Ideal für den Einsatz in Ihrem Industrie- oder Produktionsbetrieb.

Price upon inquiry

specifications

| | |
|-------------------------------|-----------------------------|
| height of center | 500 mm |
| distance between center | 1500 mm |
| bed width | 755 mm |
| max. swing over bed | 1000 mm |
| max. swing over slider | 610 mm |
| diameter of spindlehole | 130 mm |
| spindlenose | D1-15/short cone 15 |
| speed range | 3.15 - 315 U/min (21 steps) |
| range longitudinal feeds | 0.1 - 12 mm/U 57 steps |
| range cross feeds | 0.05 - 6 mm/U 57 steps |
| rapid feed longitudinal/cross | 3700/1850 mm/min |
| metric thread | 1 - 120 mm |
| inch thread | 3/8 - 28 Gtg/Inch |
| model thread | 0.5 - 60 mm |
| diametral pitch | 1 - 56 DP |
| diameter of Tailstock Quill | 160mm |
| quill konus | MK 6 |
| quill stroke | 300 mm |
| power of engine | 22 KW |
| weight | 8.000,00 kg |
| dimensions | 4950x2190x1810 mm |

equipment

- 130 mm diameter of spindlehole
- 755 mm bed width
- hydraulic spindle break
- hydraulic clutch system
- automatic feed in longitudinal and cross through one-hand-lever-technic
- Integrated taper turning device via driven upper support
- rapid feed in longitudinal and cross via Pushbutton
- overload clutch in apron
- headstock lubrication by integrated pump
- manual guideway central lubrication
- adjustable main spindle bearing
- multi-plate clutch in Hauptgearbox
- helically toothed, hardened and ground gears for little clearance and smooth running
- cooling device
- splash guard
- 4-position toolholder for lathe

accessoires

4 jaws independent chuck 1000 mm, steady rest clamping range 480 - 20 mm, following rest 20-200 mm

optional accessory

Multifix quick-change steel holder set Gr. D

1.098,00 €