

L+Z Lathe DKM 1000 S

Lassen You they throughzeugen of Kraft, Robustheit and Hatdling. Mit ourr DKM 1000 and DKM 1250 are heavy Workpiece no Thema more. Datk the russischen Bauart, the massiven construction of all Components and the heavilyen 22KW drive motor, can be with thesen machinesmodell enorme Spatleisungen erzielt will. Ideal for the insert in yourm Industrie- or Produktionsbetrieb.

Price upon inquiry

specifications

heigth of center	500 mm
distance between center	5000 mm
bed width	755 mm
max. swing over bed	1000 mm
max. swing over slider	610 mm
diameter of spindlehole	130 mm
spindlenose	D1-15/short cone 15
speed range	3.15 - 315 U/min (21 steps)
range longitudinal feeds	0.1 - 12 mm/U 57 steps
range cross feeds	0.05 - 6 mm/U 57 steps
rapid feed longitudinal/cross	3700/1850 mm/min
metric thread	1 - 120 mm
inch thread	3/8 - 28 Gatg/Inch
model thread	0.5 - 60 mm
diametral pitch	1 - 56 DP
diameter of Tailstock Quill	160mm
quill konus	MK 6
quill stroke	300 mm
power of engine	22 KW
weight	15.800,00 kg
dimensions	8350x2190x1810 mm

equipment

- 130 mm diameter of spindlehole
- 755 mm bed width
- hydraulic spindle break
- hydraulic clutch system
- automatic feed in longitudinal and cross through one-hand-lever-technic
- Integrated taper turning device via driven upper support
- rapid feed in longitudinal and cross via Pushbutton
- overload clutch in apron
- headstock lubrication by integrated pump
- manual guideway central lubrication
- adjustable main spindle bearing
- multi-plate clutch in Haupgearbox
- helically toothed, hardened and ground gears for little clearance and smooth running
- cooling device
- splash guard
- 4-position toolholder for lathe

accessoires

4 Jaw Independent Chuck 1000 mm

optinalit accessory

Multifix quick-change steel holder set Gr. D

1.098,00 €