

L+Z Lathe DKM 300.750 -1

Günstige Leit- and Feed Rodmaschine for the onzerteilreadyung and education. Das ribbede Bed guaranteed an vibrationsarmen run. Please beachten You, thes thesit machinesmodell with a elektromagnetischen spindle break according the CE Richtlinien fitted is! The machine verfügt through a securitysrelais, zero triggering and securitysstart fromschaltung with Nothalt the warehouseptspindel at Power failure, 2 stufig Main Motor.

Netto: 6.550,00 €

Result (include USt.): 7.794,50 €

plus Versatdkosten

specifications

| | |
|--------------------------|------------------------------|
| height of center | 150 mm |
| distance between center | 750 mm |
| max. swing over bed | 300 mm |
| max. swing in the gap | 430 mm |
| max. swing over slider | 178 mm |
| spindlenose | D1-4/DIN 55029 |
| diameter of spindlehole | 38 mm |
| speed range | 50 - 1810 U/min |
| Travel X-Axis | 130 mm |
| travel Z | 560 mm |
| Travel Z0 Axis | 75 mm |
| range longitudinal feeds | 0,052 - 1,392 mm/U |
| range cross feeds | 0,014 - 0,38 mm/U |
| metric thread | 0,4 - 7 mm |
| inch thread | 4 - 56 TPI |
| quill stroke | 100 mm |
| quill konus | MK 3 |
| power of engine | 1,1 + 1,5 KW (400 V 2 steps) |
| weight | 500,00 kg |
| dimensions | 1590 x 750 x 1270 mm |

equipment

- produced according DIN 8606
- double supported main spindle with 38 mm spindle bore
- adjustable Roller Bearings the main spindle
- hardened and ground gears for low-noise run
- adjustable guideways by Gibs
- Gap Bed
- ready mounted digital readout
- elektromechanical stoped main spindle according CE
- zero triggering according CE
- securitysrelais according CE
- micrometer adjustable feedstop prism

accessoires

3-jaw chuck 160mm, 4 jawsplatscheibenfutter 200 mm, adapter plate 250mm, steady and following rest, change gear set, splash guard, cooling device, auto feed stop block with Mikrometer, 3 axis digital Measuring system ready mounted, Electromechanical brake for main spindle, securitysrelais

optinalit accessory

| | |
|---|-------------------|
| clamping tool set Multifix Gr. A | 389,00 € |
| cooling device K45 | 225,00 € |
| MK3 running | 39,80 € |
| 2 mm with insert system 9- pieces | 75,00 € |
| 16 mm with insert system 9 teilig | 89,00 € |
| keyless drill chuck B16, 1-13mm | 19,00 € |
| keyless drill chuck B18 3-16mm | Preis auf Anfrage |
| reduction sleeve MK3 - B16 | 3,85 € |
| reduction sleeve MK3 - B18 | 4,20 € |
| MK3 running | Preis auf Anfrage |
| 3-B precision lathe chuck D=160, DIN6350, cast iron, one-piece jaws, frontgebohrt | Preis auf Anfrage |
| Flange DIN55029, D=125, D1-4 | 115,00 € |
| machinemount D-125 mm | Preis auf Anfrage |
| Flange DIN55029, D=160, D1-4 | 121,50 € |
| 4-B lathe chuck D=160, DIN6350, cast iron | 243,70 € |
| keyless drill chuck B18 1-16mm | 25,00 € |
| turret head set for lathes | 255,80 € |
| Combination Chucks K 62160 | 389,00 € |