

L+Z Lathe DKM 300.914 -1

Günstig onsteigermodell for the education. Please beachten
You, thes thesit machinesmodell with a electromagneticn
spindle break fitted is!

Price upon inquiry

specifications

height of center	150 mm
distance between center	914 mm
max. swing over bed	300 mm
max. swing in the gap	430 mm
max. swing over slider	180 mm
diameter of spindlehole	38 mm
spindlenose	D 1 - 4/MK 5
speed range	50 - 1810 U/min 18 steps
Travel X-Axis	130 mm
travel Z	760 mm
Travel Z0 Axis	75 mm
range longitudinal feeds	0,052 - 1,392 mm/U
range cross feeds	0,014 - 0,38 mm/U
metric thread	0,4 - 7 mm
inch thread	4 - 56 TPI
quill stroke	100 mm
quill konus	MK 3
power of engine	1,1 + 1,5 KW (400V 2 steps)
weight	560,00 kg
dimensions	1800 x 750 x 1270 mm

equipment

- produced according DIN 8606
- 38 mm spindle bore
- Zahlrätthe hardend and ground
- adjustable guideways by Gibs
- elektro mechatisch stoped main spindle
- adjustable main spindle bearing
- Gap Bed
- digital readout

accessoires

3-jaw chuck 160mm, 4 jawsplatscheibenfutter 200 mm, adapter plate 250mm, steady and following rest, change gear set, splash guard, cooling device, auto feed stop block with Mikrometer, 3 axis digital Measuring system ready mounted, Electromechanical brake for mainspindle

optinalit accessory

clamping tool set Multifix Gr. A	389,00 €
2 mm with insert system 9- pieces	75,00 €
16 mm with insert system 9 teilig	89,00 €
reduction sleeve MK3 - B16	3,85 €
reduction sleeve MK3 - B18	4,20 €
MK3 running	Preis auf Anfrage
3-B precision lathe chuck D=160, DIN6350, cast iron, one-piece jaws, frontgebohrt	Preis auf Anfrage
Flange DIN55029, D=125, D1-4	115,00 €
machinemount D-125 mm	Preis auf Anfrage
Flange DIN55029, D=160, D1-4	121,50 €
4-B lathe chuck D=160, DIN6350, cast iron	243,70 €
C5 DIN6350 with 24 collets	369,00 €
turret head set for lathes	255,80 €