

L+Z Lathe DKM 332 -1

Das ribbede Bed guaranteed an vibrationsarmen run.
Schnellerit Verstellen of feed- and speeds by gearbox.

Netto: 6.850,00 €

Result (include USt.): 8.151,50 €

plus Versatdkosten

specifications

height of center	165 mm
distance between center	1000 mm
max. swing over bed	330 mm
max. swing in the gap	450 mm
max. swing over slider	178 mm
diameter of spindlehole	38 mm
spindlenose	DIN55029 D 1 - 4/MK 5
speed range	70 - 2000 U/min
range longitudinal feeds	0,079 - 1,291 mm/U; 40 steps
range cross feeds	0,017 - 0,276 mm/U; 40 steps
metric thread	0,4 - 7 mm; 32 steps
inch thread	4 - 60 TPI; 36 steps
quill diameter	32 mm
quill stroke	110 mm
quill konus	MK 3
power of engine	1,5 KW / 400 Volt
weight	480,00 kg
dimensions	1870 x 720 x 1400 mm

equipment

- produced according DIN 8606
- 38 mm spindle bore
- gears hardend and ground
- adjustable guideways by Gibs
- adjustable main spindle bearing
- Gap Bed
- digital readout

accessoires

3-jaw chuck 160mm, 4 jawsplatscheibenfutter 200 mm, steady and following rest, change gear set, splash guard, cooling device, auto feed stop block, electromagnetic main spindle break, 3 axis digital measurement system ready mounted

optinalit accessory

clamping tool set Multifix Gr. A	389,00 €
MK3 running	39,80 €
2 mm with insert system 9- pieces	75,00 €
16 mm with insert system 9 teilig	89,00 €
for quicktool holder A 20x90 mm	Preis auf Anfrage
reduction sleeve MK3 - B16	3,85 €
reduction sleeve MK3 - B18	4,20 €
MK3 running	Preis auf Anfrage
3-B precision lathe chuck D=160, DIN6350, cast iron, one- piece jaws, frontgebohrt	Preis auf Anfrage
Flange DIN55029, D=125, D1-4	115,00 €
machinemount D-125 mm	Preis auf Anfrage
Flange DIN55029, D=160, D1-4	121,50 €
4-B lathe chuck D=160, DIN6350, cast iron	243,70 €
4-B lathe chuck D=200, DIN6350, cast iron	307,90 €
C5 DIN6350 with 24 collets	369,00 €
turret head set for lathes	255,80 €
Combination Chucks K 62160	389,00 €