

# DKM 410L



# DKM 410L

## SPECIFICATIONS

height of center	205 mm
distance between center	1000 mm
max. swing over bed	410 mm
max. swing in the gap	530 mm
max. swing over slider	240 mm
movement of X-axis	235 mm
movement Z0-Axis	132 mm
diameter of spindlehole	52 mm
spindlenose	D1-5 DIN 55029
speed range	55-2000 U/min
range longitudinal feeds	0.053 - 1-291 mm/U; 40 steps
range cross feeds	0.011 - 0.276 mm/U; 40 steps
metric thread	0.4 - 7 mm; 32 steps
inch thread	4 - 60 TPI; 36 steps
quill diameter	32 mm
quill stroke	120 mm
quill konus	MK 4
power of engine	2.2 KW / 400 Volt
weight	820,00 kg
dimensions	1900x800x1280 mm

## EQUIPMENT

- » 3 axis digital measurement system ready mounted
- » electromagnetic main spindle break
- » autofeed in longitudinal and crossrichtung
- » securitysrelais
- » micrometer stop block
- » cooling device
- » 3-Jaws lathe chuck with each 1 Set turn- and Drill jaws
- » steady + following rest



## ACCESSOIRES

3 axis digital measurement system ready mounted, automatic feed in longitudinal and cross direction, micrometer adjustable stop block, 3-Jaws lathe chuck 200 mm include each 1 Set turn- and Drill jaws, cooling device, electromagnetic main spindle break, steady + following rest, german manual.

## OPTIONAL ACCESSORY

- » Quick change tool holder set Gr. A clamping tool set Multifix Gr. A