

DKM 410LS



DKM 410LS

SPECIFICATIONS

height of center	200 mm
distance between center	1000 mm
max. swing over bed	400 mm
max. swing in the gap	550 mm
max. swing over slider	264 mm
movement of X-axis	180 mm
movement Z0-Axis	95 mm
diameter of spindlehole	51 mm
spindlenose	D1-5
speed range	45-1800 U/min
range longitudinal feeds	0.043 - 0.653 mm/U; 42 steps
range cross feeds	0.027 - 0.413 mm/U
metric thread	0.4 - 7 mm; 42 steps
inch thread	4 - 56 TPI; 28 steps
quill diameter	45 mm
quill stroke	100 mm
quill konus	MK 3
power of engine	2.4 KW / 400 Volt
weight	900,00 kg
dimensions	1935x750x1500 mm

EQUIPMENT

- » 3 axis digital measurement system ready mounted
- » electromagnetic main spindle break
- » autofeed in longitudinal and crossrichtung
- » securitysrelais
- » micrometer stop block
- » cooling device
- » 3-Jaws lathe chuck with each 1 Set turn- and Drill jaws
- » steady + following rest



ACCESSOIRES

3 axis digital measurement system ready mounted, automatic feed in longitudinal and cross direction, micrometer adjustable stop block, 3-Jaws lathe chuck 200 mm include each 1 Set turn- and Drill jaws, cooling device, electromagnetic main spindle break, steady + following rest, german manual.