

## L+Z Lathe DKM 410Sx1000

Leit- and Feed Roddrehmaschine with 52 mm spindle bore and kräftigem 4.0 KW Motor. Fastground guideways, verschleißfreie electronical spindle break. The Bitte Alternative to a Lathe of german Herstellung!

**Netto: 16.200,00 €**

**Result (include USt.): 19.278,00 €**

plus Versatdkosten

### specifications

heigth of center	210 mm
distance between center here	1000 mm also in 750 or. 1500 mm possible
max. swing over bed	410 mm
max. swing over slider	240 mm
movement of X-axis	247 mm
Z1 axis travel	124 mm
diameter of spindlehole	52 mm
spindlenose	Camlock D1 - 6
speed range	32 - 2000 U/min (12 steps)
range longitudinal feeds	0.03 - 0.89 mm/U in 40 steps
range cross feeds	0.015 - 0.045 in 40 steps
metric thread	0.4 - 14 mm in 53 steps
inch thread	2 - 56 Gatg/Inch in 40 steps
Diamental	4 - 56 D.P. in 50 steps
quill diameter	55 mm
quill stroke	120 mm
quill konus	MK 4
power of engine	4.0 KW 400 Volt
weight	1.985,00 kg
dimensions	2270 x 1143 x 1295 mm

### equipment

- 52 mm spindle bore
- gears hardend and ground
- manual guideway lubricationschmierung
- adjustable main spindle bearing
- overload clutch in apron
- Mehrfach-auto feed stop block
- digital readout

### accessoires

3-jaw chuck 200mm, 4 jawsplatscheibenfutter 250 mm, steady and following rest, splash guard, cooling device, change gear set, 3 axis digital measurement system ready mounted, Mehrfach-auto feed stop blocksystem, german Operating documents, CE EC declaration of conformity