

# DKM 460Sx1500



# DKM 460Sx1500

## SPECIFICATIONS

<b>height of center</b>	229 mm
<b>distance between center here</b>	1500 mm
<b>max. swing over bed</b>	458 mm
<b>swing over bed in the Gap Bed</b>	640 mm
<b>length the Gap Bed</b>	155 mm
<b>max. swing over slider</b>	380 mm
<b>diameter of spindlehole</b>	77 mm
<b>spindlenose</b>	Camlock D1 - 8
<b>speed range</b>	24 - 1600 U/min (12 steps)
<b>Travel Z0 Axis</b>	120 mm
<b>Travel X-Axis</b>	230 mm
<b>range longitudinal feeds</b>	0.03 - 0.89 mm/U in 40 steps
<b>range cross feeds</b>	0.015 - 0.045 in 40 steps
<b>metric thread</b>	0.4 - 14 mm in 53 steps
<b>inch thread</b>	2 - 56 Gatg/Inch in 40 steps
<b>Diametral</b>	4 - 56 D.P. in 50 steps
<b>quill diameter</b>	55 mm
<b>quill stroke</b>	120 mm
<b>quill konus</b>	MK 4
<b>power of engine</b>	5.5 KW 400 Volt
<b>weight</b>	2.450,00 kg
<b>dimensions</b>	2770 x 980 x 1210 mm

## EQUIPMENT

- » 77 mm spindle bore
- » elektro-mechanical spindle break
- » gears hardend and ground
- » manual guideway lubricationschmierung
- » adjustable main spindle bearing
- » overload clutch in apron
- » digital readout



## ACCESSORIES

3-jaw chuck 250mm, 4 jawsplatscheibenfutter 315 mm, steady and following rest, splash guard, cooling device, change gear set, 3 axis digital measurement system ready mounted