

L+Z Lathe DKM 460Sx1500

Leit- and Feed Roddrehmaschine with 77 mm spindle bore and kräftigem 5.5 KW Motor. Fastground guideways, verschleißfreie electronical spindle break and soft Start. The Bitte Alternative to a Lathe of german Herstellung!

Netto: 21.450,00 €

Result (include USt.): 25.525,50 €

plus Versatdkosten

specifications

| | |
|-------------------------------|------------------------------|
| heigth of center | 229 mm |
| distance between center here | 1500 mm |
| max. swing over bed | 458 mm |
| swing over bed in the Gap Bed | 640 mm |
| length the Gap Bed | 155 mm |
| max. swing over slider | 380 mm |
| diameter of spindlehole | 77 mm |
| spindlenose | Camlock D1 - 8 |
| speed range | 24 - 1600 U/min (12 steps) |
| Travel Z0 Axis | 120 mm |
| Travel X-Axis | 230 mm |
| range longitudinal feeds | 0.03 - 0.89 mm/U in 40 steps |
| range cross feeds | 0.015 - 0.045 in 40 steps |
| metric thread | 0.4 - 14 mm in 53 steps |
| inch thread | 2 - 56 Gatg/Inch in 40 steps |
| Diamental | 4 - 56 D.P. in 50 steps |
| quill diameter | 55 mm |
| quill stroke | 120 mm |
| quill konus | MK 4 |
| power of engine | 5.5 KW 400 Volt |
| weight | 2.450,00 kg |
| dimensions | 2770 x 980 x 1210 mm |

equipment

- 77 mm spindle bore
- elektro-mechanical spindle break
- gears hardend and ground
- manual guideway lubricationschmierung
- adjustable main spindle bearing
- overload clutch in apron
- digital readout

accessoires

3-jaw chuck 250mm, 4 jawsplatscheibenfutter 315 mm, steady and following rest, splash guard, cooling device, change gear set,3 axis digital measurement system ready mounted