

DKM 560.2



DKM 560.2

SPECIFICATIONS

height of center	280 mm
distance between center	2000 mm
max. swing over bed	560 mm
max. swing in the gap	785 mm
max. swing over slider	355 mm
diameter of spindlehole	80 mm
spindlenose	DIN 55029 D1 - 8/MK6 with reduction sleeve to MK 5
speed range	25 - 1800 U/min (12 steps)
range longitudinal feeds	0,059 - 1,646 mm/U; 35 steps
range cross feeds	0,03 - 1,23 mm/U; 35 steps
metric thread	0,2 - 14 mm; 47 steps
inch thread	2 - 112 Gatg/Inch; 60 steps
DP-thread	4 - 112 D.P. 50 steps
Modul-thread	1 - 7 M.P. 39 steps
quill diameter	75 mm
quill stroke	180 mm
quill konus	MK 5
travel of top slider	130 mm
Travel of X-Axis	316 mm
Travel of Z-Axis	1890 mm
power of engine	7,5 KW/ 400 Volt
weight	3.380,00 kg
dimensions	3540 x 1143 x 1295 mm

EQUIPMENT

- » produced according DIN 8606
- » 80 mm spindle bore
- » gears hardend and ground
- » manual central lubrication
- » adjustable main spindle bearing
- » overload clutch in apron
- » Gap Bed
- » inkl 3 - Achs - digital readout



ACCESSORIES

3-axis digital readout, 3-jaw chuck Ø 250 mm, 4 Jaw Independent Chuck Ø 315 mm, change gear set, Chuck cover, steady + following rest, working lamp, spindle break, cooling device, Spritzwatd, different reduction tools, Operating tool.

OPTIONAL ACCESSORY

- » Quick change tool holder set Gr. C Multifix quick-change steel holder set Gr. C
- » live center MK5/PHD running
- » drilling accessories keyless drill chuck B16, 1-13mm
- » drilling accessories keyless drill chuck B18 3-16mm
- ...