

# DKM 800 CL





# DKM 800 CL

## SPECIFICATIONS

height of center	400 mm
distance between center	2000 mm
bed width	500 mm
max. swing over bed	800 mm
max. swing in the gap	1000 mm
max. swing over slider	560
diameter of spindlehole	103 mm
spindlenose	DIN 55029 Camlock D1-8
speed range	30 - 1400 U/min (12)
range longitudinal feeds	0,063 - 2,52 mm/U (65 steps)
range cross feeds	0,027 - 1,07 mm/U (65 steps)
metric thread	1 - 14 mm (22 steps)
inch thread	28 - 2 Gatg/Inch (24 steps)
model thread	0,5 - 7 mm (18 steps)
diametral pitch	56 - 4 DP (24 steps)
quill diameter	90 mm
quill stroke	150 mm
quill konus	morse cone 5
power of engine	7,5 KW
weight	3.150,00 kg
dimensions	3800x1150x2000 mm

## EQUIPMENT

- » rapid feed in longitudinal and cross
- » adjustable main spindle bearing
- » gears diagonally dovetailed, hardened and ground
- » multi-plate clutch adjustable
- » headstock lubrication by integrated pump
- » overload clutch in apron
- » Gap Bed
- » splashguard
- » 3 axis digital measurement system
- » cooling device



## ACCESSORIES

3-jaw chuck 315mm,  
4 jawsplatscheibenfutter 500 mm,  
steady and following rest

## OPTIONAL ACCESSORY

- » Quick change tool holder set Gr. C Multifix quick-change steel holder set Gr. C
- » live center MK5/PHD running
- » drilling accessories keyless drill chuck B16, 1-13mm
- » drilling accessories keyless drill chuck B18 3-16mm

...