

L+Z Lathe DKM 800 CL

Wenn ihre Anforderungen kraftvolle torque, optimal cutsrgebnisse and high cutting forceen are, is our DKM 800 the the richtige for You. Durch the flexiblen onstell- and Anpassungsspossiblekeiten and ihren big spindle bore is machine universal and optimal as Industrie- or Produktionsdrehmaschine for onzelteil- or seriesnreadyung asetzbar.

Netto: 32.500,00 €

Result (include USt.): 38.675,00 €

plus Versatdkosten

specifications

height of center	400 mm
distance between center	2000 mm
bed width	500 mm
max. swing over bed	800 mm
max. swing in the gap	1000 mm
max. swing over slider	560
diameter of spindlehole	103 mm
spindlenose	DIN 55029 Camlock D1-8
speed range	30 - 1400 U/min (12)
range longitudinal feeds	0,063 - 2,52 mm/U (65 steps)
range cross feeds	0,027 - 1,07 mm/U (65 steps)
metric thread	1 - 14 mm (22 steps)
inch thread	28 - 2 Gatg/Inch (24 steps)
model thread	0,5 - 7 mm (18 steps)
diametral pitch	56 - 4 DP (24 steps)
quill diameter	90 mmm
quill stroke	150 mm
quill konus	morse cone 5
power of engine	7,5 KW
weight	3.150,00 kg
dimensions	3800x1150x2000 mm

equipment

- rapid feed in longitudinal and cross
- adjustable main spindle bearing
- gears diagonallydovetailed , hardend and ground
- multi-plate clutch adjustable
- headstock lubrication by integrated pump
- overload clutch in apron
- Gap Bed
- splashguard
- 3 axis digital measurement system
- cooling device

accessoires

3-jaw chuck 315mm, 4 jawsplatscheibenfutter 500 mm, steady and following rest

optinalit accessory

Multifix quick-change steel holder set Gr. C	849,00 €
MK5/PHD running	89,00 €
keyless drill chuck B16, 1-13mm	19,00 €
keyless drill chuck B18 3-16mm	Preis auf Anfrage
reduction sleeve MK5 - B18	14,00 €
MK5 running	129,00 €
Flange DIN55029, D=315, D1-8	411,30 €
4-B lathe chuck D=400, DIN6350, cast iron	1.014,20 €
Flange DIN55029, D=400, D1-8	716,70 €
keyless drill chuck B18 1-16mm	25,00 €
Combination Chucks K 62325	Preis auf Anfrage
Flange DIN55029, D=500, D1-8	931,60 €