

## L+Z Lathe DKM 800 L

Wenn ihre Anforderungen kraftvolle torque, optimal cutsrgebnisse and high cutting forceen are, is our DKM 800 the the richtige for You. Durch the flexiblen onstell- and Anpassungsspossiblekeiten and ihren big spindle bore is machine universal and optimal as Industrie- or Produktionsdrehmaschine for onzelteil- or seriesnreadyung asetzbar.

**Netto: 33.850,00 €**

**Result (include USt.): 40.281,50 €**

plus Versatdkosten

### specifications

height of center	400 mm
distance between center	3000 mm
bed width	500 mm
max. swing over bed	800 mm
max. swing in the gap	1000 mm
max. swing over slider	560
diameter of spindlehole	82 mm
spindlenose	DIN 55029 Camlock D1-8
speed range	30 - 1400 U/min (24)
range longitudinal feeds	0,028 - 6,43 mm/U (93 steps)
range cross feeds	0,012 - 2,73 mm/U (93 steps)
metric thread	0,5 - 224 mm (48 steps)
inch thread	72 - 1/8 Gatg/Inch (49 steps)
model thread	0,5 - 112 mm (42 steps)
diametral pitch	56 - 1/4 DP
quill diameter	90 mm
quill stroke	150 mm
quill konus	morse cone 5
power of engine	7,5 KW
weight	4.000,00 kg
dimensions	4565x1340x1430 mm

### equipment

- rapid feed in longitudinal and cross
- adjustable main spindle bearing
- gears diagonallydovetailed , hardend and ground
- multi-plate clutch adjustable
- headstock lubrication by integrated pump
- overload clutch in apron
- Gap Bed
- splashguard
- 3-axis digital measurement system
- cooling device

### accessoires

3-jaw chuck 315mm, 4-jaw independent chuck 500mm, steady and following rest