

crossdrehmaschine DKM 1600 P CNC/FANUC

CNC Kopfdrehmaschine in robust bauweise and heavilyem 22 KW Motor. The machine is for heavy Spataratten best suitable.

Price upon inquiry

specifications

| | |
|-------------------------|------------------------|
| heigth of center | 800 mm |
| processings länge max. | 1000 mm |
| max. swing over bed | 1600 mm |
| max. swing over slider | 680 mm |
| spindlenose | A 2/15 (8xM22) |
| speed range | 2 - 200 U/min stepless |
| travel cross | 820 mm |
| longitudinal movement | 1000 mm |
| travel of Top Slider | 400 mm |
| longitudinal feed | 0.8 - 25 mm/min |
| cross feed | 1.6 - 50 mm/min |
| rapid feed longitudinal | 2500 mm/min |
| Toolholder swiveling | 360° |
| power of engine | 22 KW optional 30 KW |
| weight | 8.300,00 kg |
| dimensions | 3800 x 2600 x 2200 mm |

equipment

- gears diagonallydovetailed , hardend and ground
- lubrication by integrated pump
- adjustable main spindle bearing
- rapid feed in longitudinal
- FANUC OI MATE

accessoires

control system Fanuc Mate 0I, 4-jaw independent chuck 1600mm, cooling device, working lamp