

RKM 10025



HIGHLIGHTS

- » heavy Industrie radial arm drill press
- » high class processed for best lifetime

RKM 10025

SPECIFICATIONS

drilling capacity in steel	100 mm
spindle speeds	8 - 1000 U/min
dimension working table	1000x800x560 mm
dimensions-Fuss	2750x1220x300 mm
weight cube table	1040 kg
spindle adapter	morse cone 6
quill stroke	500 mm
automatic feeds	0.06 - 3.2 mm/U
distance spindle nose - table surface	750 - 2500 mm
swivel arm	360°
distance spindle nose - column	2500mm
power of engine	15 KW
distance spindle nose - base	570 - 3150mm
thread cutting in Steel until	M 70
thread cutting in cast iron until	M 80
horizontal travel of Drilling Head	2580 mm
vertical travel of Arm	1000 mm
weight	20.000,00 kg
dimensions	4780x1630x4720 mm

EQUIPMENT

- » guideways hardend and ground
- » height adjustment motorized
- » Hydraulic change feed- and Spindlegearbox
- » hydraulic and mechanical Brakes
- » hardened and ground gears
- » ground Base
- » thick-walled, ground Column
- » height adjustment of the radial arm with strokemotor
- » radial arm and drilling head with hydraulic Brake
- » hardened and ground gears in in Oil running

ACCESSOIRES

Cube table, Cooling device

OPTIONAL ACCESSORY

- » drilling accessories keyless drill chuck B16, 1-13mm
- » drilling accessories keyless drill chuck B18 3-16mm
- » other tools reduction sleeve MK4 - B18
- » other tools reduction sleeve MK4 - B16
- » other tools reduction sleeve MK4 - MK3
- ...