

RKM 5016



HIGHLIGHTS

- » heavy Industrie radial arm drill press
- » high class processed for best lifetime




RKM 5016

SPECIFICATIONS

drilling capacity in steel	50mm
spindle speeds	25 - 2000 U/min (500Nm)
dimension cube table	1700 x 980 mm
dimension working table	630 x 500 x 500 mm
spindle adapter	morse cone 5
quill stroke	315 mm
automatic feeds	0.04 - 3.2 U/min (16 steps)
distance spindle nose - column	350-1600 mm
distance spindle nose - table	350-1250 mm
surface	
swivel arm	360°
distance spindle nose - column	1600 mm
power of engine	3,5 KW/400 Volt
distance spindle nose - base	350 - 1250mm
horizontal travel drilling head	1250 mm
vertical travel of Arm	900 mm
weight	3.500,00 kg
dimensions	2490 x 1050 x 2835 mm

EQUIPMENT

- » guideways hardend and ground
- » height adjustment motorized
- » Hydraulic change feed- and Spindlegearbox
- » hydraulic and mechanical Brakes
- » hardened and ground gears
- » ground Base
- » thick-walled, ground Column
- » height adjustment of the radial arm with strokemotor
- » radial arm and drilling head with hydraulic Brake



ACCESSORIES

Cube table, Cooling device

OPTIONAL ACCESSORY

- » drilling accessories keyless drill chuck B16, 1-13mm
- » drilling accessories keyless drill chuck B18 3-16mm
- » other tools reduction sleeve MK4 - B18
- » other tools reduction sleeve MK4 - B16
- » other tools reduction sleeve MK4 - MK3
- » ...