

RKM 6320



HIGHLIGHTS

- » heavy Industrie radial arm drill press
- » high class processed for best lifetime

RKM 6320

SPECIFICATIONS

drilling capacity in steel	63mm
spindle speeds	20 - 1600 U/min; 22 steps (980Nm)
dimensions cube table	630 x 500 x 500 mm
spindle adapter	morse cone 5
quill stroke	405 mm
automatic feeds	0.04 - 3.2 U/min; 16 steps
distance spindle nose - column	450-2000 mm
distance spindle nose - table surface	400-1600 mm
swivel arm	360°
distance spindle nose - column	2000 mm
power of engine	5,5 KW/400 Volt
distance spindle nose - base	400 - 1600 mm
thread cutting in Steel until	M 56
thread cutting in cast iron until	M 60
horizontal travel of Drilling Head	1550 mm
vertical travel of Arm	1200 mm
dimensions machinemount	3080x1250x300 mm
weight	7.000,00 kg
dimensions	3080 x 1250 x 3205 mm



EQUIPMENT

- » guideways hardend and ground
- » height adjustment motorized
- » Hydraulic change feed- and Spindlegearbox
- » hydraulic and mechanical Brakes
- » hardened and ground gears
- » ground Base
- » thick-walled, ground Column
- » height adjustment of the radial arm with strokemotor
- » radial arm and drilling head with hydraulic Brake
- » hardened and ground gears in in Oil running
- » guideways at radial arm hardend and ground

ACCESSOIRES

Cube table, Cooling device

OPTIONAL ACCESSORY

- » drilling accessories keyless drill chuck B16, 1-13mm
- » drilling accessories keyless drill chuck B18 3-16mm
- » other tools reduction sleeve MK4 - B18
- » other tools reduction sleeve MK4 - B16
- » other tools reduction sleeve MK4 - MK3
- ...