

RKM 8025



HIGHLIGHTS

- » heavy Industrie radial arm drill press
- » high class processed for best lifetime

RKM 8025

SPECIFICATIONS

drilling capacity in steel	80mm
spindle speeds	16 - 1250 U/min (1568Nm)
dimension working table	1000x800x560 mm
dimensions machinemount	2750x1220x300 mm
weight cube table	800 kg
spindle adapter	morse cone 6
quill stroke	450 mm
automatic feeds	0.04 - 3.2 U/min (16 steps)
distance spindle nose - column	500-2500 mm
distance spindle nose - table	550-2000 mm
surface	
swivel arm	360°
distance spindle nose - column	2500 mm
power of engine	7,5 KW/400 Volt
distance spindle nose - base	550 - 2000mm
thread cutting in Steel until	M52
Gewaof thechneithe in cast iron until	M60
horizontaler travel drilling head	2000 mm
vertical travel of Arm	1450 mm
dimensions machinemount	3730x1400 mm
weight	11.000,00 kg
dimensions	3730 x 1400 x 3795 mm

EQUIPMENT

- » guideways hardend and ground
- » height adjustment motorized
- » Hydraulic change feed- and Spindlegearbox
- » hydraulic and mechanical Brakes
- » hardened and ground gears
- » ground Base
- » thick-walled, ground Column
- » height adjustment of the radial arm with strokemotor
- » radial arm and drilling head with hydraulic Brake
- » hardened and ground gears in in Oil running
- » guideways at radial arm hardend and ground
- » automatic quill feed

ACCESSOIRES

Cube table, Cooling device

OPTIONAL ACCESSORY

- » drilling accessories keyless drill chuck B16, 1-13mm
- » drilling accessories keyless drill chuck B18 3-16mm
- » other tools reduction sleeve MK4 - B18
- » other tools reduction sleeve MK4 - B16
- » other tools reduction sleeve MK4 - MK3
- ...