

DKM 1600



DKM 1600

SPECIFICATIONS

height of center	800 mm
distance between center	2000 mm
bed width	755 mm
max. swing over bed	1600 mm
max. swing over slider	1240 mm
diameter of spindlehole	130 mm
spindlenose	A 215/8xM22
speed range	3.15 - 315 U/min
range longitudinal feeds	0.1 - 12 mm/U 56 steps
range cross feeds	0.05 - 6 mm/U 56 steps
metric thread	1 - 120 mm/ 44 steps
inch thread	28 - 1/4 Gatg/Inch;31 steps
model thread	0.5 - 60 mm;45 steps
diametral pitch	1/2 - 56 DP;38 steps
quill diameter	200 mm
quill stroke	300 mm
quill konus	morse cone 6
power of engine	22 KW
weight	12.100,00 kg
dimensions	5100 x 2150 x 1700 mm

EQUIPMENT

- » 130 mm diameter of spindlehole
- » 755 mm bed width
- » hydraulic spindle break
- » hydraulic clutch system
- » automatic feed in longitudinal and cross through one-hand-lever-technic
- » Integrated taper turning device via driven upper support
- » electric driven Tailstock
- » rapid feed in longitudinal and cross via Pushbutton
- » overload clutch in apron
- » headstock lubrication by integrated pump
- » manual guideway central lubrication

ACCESSOIRES

4-jaw independent chuck 1250mm