

## heavy duty lahe DKM 1800S x 10000

Universaldrehmaschine for big turning diameter with a diameter of spindlehole of 130 mm. Theses machinesmodell allows by been 30 KW drive motor, the hydraulic clutches- and Brakesystem, such as the bed width of 1100 mm the processing of big Workpieces with high Spatstart fromnahme. Es are turning diameter of until to 3.500mm possible.

### Price upon inquiry

#### specifications

|                                 |                         |
|---------------------------------|-------------------------|
| height of center                | 900 mm                  |
| distance between center         | 10000 mm                |
| bed width                       | 1100 mm                 |
| Swing- $\emptyset$ over bed     | 1800 mm                 |
| Swing- $\emptyset$ over support | 1400 mm                 |
| diameter of spindlehole         | 130 mm                  |
| speed range                     | 2 - 200 U/min           |
| spindlenose                     | A2-15                   |
| range longitudinal feeds        | (97) 0,032 - 12 m/U     |
| range cross feeds               | (97) 0,016 - 6 m/U      |
| metric thread                   | (45) 1 - 120 mm         |
| inch thread                     | (42) 1/4 - 30 Gatg/Inch |
| model thread                    | (46) 0,5 - 60 mm        |
| diametral pitch                 | (48) 0,5 - 60 DP        |
| quill diameter                  | 200 mm                  |
| quill stroke                    | 300 mm                  |
| quill konus                     | MK 6                    |
| power of engine                 | 22 KW optional 30 KW    |

#### accessoires

4-jaw independent chuck 1400 mm, steady rest  $\emptyset$  150-600 mm, following rest  $\emptyset$  50-220mm, cooling device, Quick feed for Apron, electric driven Tailstock, automatic limit switch in Z-axis optional: steady rest  $\emptyset$  260 - 900mm