

DKM 2000



DKM 2000

SPECIFICATIONS

height of center	1000 mm
distance between center	2000 mm
bed width	1100 mm
max. swing over bed	2000 mm
max. swing over slider	1600 mm
diameter of spindlehole	100 mm
spindlenose	A2-15
speed range	2,5 - 250 U/min in 21 steps
range longitudinal feeds	(97) 0,032 - 12 m/U
range cross feeds	(97) 0,016 - 6 m/U
metric thread	(45) 1 - 120 mm
inch thread	(42) 1/4 - 30 Gatg/Inch
model thread	(46) 0,5 - 60 mm
diametral pitch	(48) 0,5 - 60 DP
quill diameter	200 mm
quill stroke	300 mm
quill konus	80/1:7
power of engine	30 KW
weight	19.800,00 kg
dimensions	5120 x 2200 x 2400 mm

EQUIPMENT

- » big bed width of 1100 mm
- » Gears with helical teeth, hardened and ground
- » hydraulic clutch system pressure adjustable
- » hydraulic spindle break pressure adjustable
- » lubrication by integrated pump
- » adjustable main spindle bearing
- » rapid feed in longitudinal and cross
- » overload clutch in apron
- » 4 - axis - digital readout

ACCESSOIRES

4-jaw independent chuck 1600 mm, steady rest Ø 220-630 mm, following rest Ø 50-220mm, cooling device, Quick feed for Apron, electric driven Tailstock

optional: steady rest Ø 260 - 1100mm

OPTIONAL ACCESSORY

- » Quick change tool holder set Gr. D Multifix quick-change steel holder set Gr. D