

# DKM 2200.10C



# DKM 2200.10C

## SPECIFICATIONS

<b>height of center</b>	1100 mm
<b>distance between center</b>	10000 mm
<b>bed width</b>	1100 mm
<b>Swing-Ø over bed</b>	2200 mm
<b>Swing-Ø over support</b>	1800 mm
<b>diameter of spindlehole</b>	260 mm
<b>speed range</b>	2,5 - 250 U/min
<b>spindlenose</b>	A2-15
<b>range longitudinal feeds</b>	(97) 0,032 - 12 m/U
<b>range cross feeds</b>	(97) 0,016 - 6 m/U
<b>metric thread</b>	(45) 1 - 120 mm
<b>inch thread</b>	(42) 1/4 - 30 Gatg/Inch
<b>model thread</b>	(46) 0,5 - 60 mm
<b>diametral pitch</b>	(48) 0,5 - 60 DP
<b>quill diameter</b>	240 mm
<b>quill stroke</b>	300 mm
<b>quill konus</b>	80/1:7
<b>power of engine</b>	40 KW
<b>weight</b>	38.500,00 kg
<b>dimensions</b>	14620 x 2380 x 2510 mm

## ACCESSOIRES

4-jaw independent chuck 2000 mm, steady rest Ø 500 - 1100 mm, steady rest 1100 - 1800 mm, cooling device, Quick feed for Apron, automatic feed in obersupport, electric driven Tailstock, 3 axis digital measurement system ready mounted.

optional: steady rest Ø 260 - 630 mm

## OPTIONAL ACCESSORY

» Quick change tool holder set Gr. D Multifix quick-change steel holder set Gr. D