

DKM 2200



DKM 2200

SPECIFICATIONS

| | |
|---------------------------------|-------------------------|
| height of center | 1100 mm |
| distance between center | 5000 mm |
| bed width | 1100 mm |
| Swing-ø over bed | 2200 mm |
| Swing-ø over support | 1800 mm |
| diameter of spindlehole | 140 mm |
| speed range | 2,5 - 250 U/min |
| spindlenose | A2-15 |
| range longitudinal feeds | (97) 0,032 - 12 m/U |
| range cross feeds | (97) 0,016 - 6 m/U |
| metric thread | (45) 1 - 120 mm |
| inch thread | (42) 1/4 - 30 Gatg/Inch |
| model thread | (46) 0,5 - 60 mm |
| diametral pitch | (48) 0,5 - 60 DP |
| quill diameter | 240 mm |
| quill stroke | 300 mm |
| quill konus | 80/ 1 to 7 |
| power of engine | 22 KW/ AC |
| weight | 30.400,00 kg |
| dimensions | 9920 x 2480 x 2610 mm |



ACCESSOIRES

4-jaw independent chuck 2000 mm, steady rest
Ø 220-630 mm, following rest Ø 50-220mm,
cooling device, Quick feed for Apron, electric
driven Tailstock

optional: steady rest Ø 900 -
1600mm, Rollerbock 800 - 1800 mm, Taper
Attachment

OPTIONAL ACCESSORY

» Quick change tool holder set Gr. D Multifix quick-
change steel holder set Gr. D