

# DKM 2400



# DKM 2400

## SPECIFICATIONS

<b>height of center</b>	1200 mm
<b>distance between center</b>	5000 mm
<b>bed width</b>	1100 mm
<b>Swing-Ø over bed</b>	2400 mm
<b>Swing-Ø over support</b>	2030 mm
<b>diameter of spindlehole</b>	140 mm
<b>speed range</b>	2,5 - 250 U/min
<b>spindlenose</b>	A2-15
<b>range longitudinal feeds</b>	(97) 0,032 - 12 m/U
<b>range cross feeds</b>	(97) 0,016 - 6 m/U
<b>metric thread</b>	(45) 1 - 120 mm
<b>inch thread</b>	(42) 1/4 - 30 Gatg/Inch
<b>model thread</b>	(46) 0,5 - 60 mm
<b>diametral pitch</b>	(48) 0,5 - 60 DP
<b>quill diameter</b>	240 mm
<b>quill stroke</b>	300 mm
<b>quill konus</b>	80/ 1 to 7
<b>power of engine</b>	22 KW/ AC
<b>weight</b>	34.400,00 kg
<b>dimensions</b>	9920 x 2580 x 2710 mm

## ACCESSOIRES

4-jaw independent chuck 2000 mm, steady rest  
Ø 220-630 mm, following rest Ø 50-220mm,  
cooling device, Quick feed for Apron, electric  
driven Tailstock

optional: steady rest Ø 900 -  
1600mm, Rollerbock 800 - 1800 mm, Taper  
Attachment

## OPTIONAL ACCESSORY

» Quick change tool holder set Gr. D Multifix quick-  
change steel holder set Gr. D