

DKM 2400



DKM 2400

SPECIFICATIONS

height of center	1200 mm
distance between center	6000 mm
bed width	1100 mm
Swing-Ø over bed	2400 mm
Swing-Ø over support	2030 mm
diameter of spindlehole	140 mm
speed range	2,5 - 250 U/min
spindlenose	A2-15
range longitudinal feeds	(97) 0,032 - 12 m/U
range cross feeds	(97) 0,016 - 6 m/U
metric thread	(45) 1 - 120 mm
inch thread	(42) 1/4 - 30 Gatg/Inch
model thread	(46) 0,5 - 60 mm
diametral pitch	(48) 0,5 - 60 DP
quill diameter	240 mm
quill stroke	300 mm
quill konus	80/ 1 to 7
power of engine	22 KW/ AC
weight	36.600,00 kg
dimensions	10920 x 2480 x 2610 mm

ACCESSOIRES

4-jaw independent chuck 2000 mm, steady rest
Ø 220-630 mm, following rest Ø 50-220mm,
cooling device, Quick feed for Apron, electric
driven Tailstock

optional: steady rest Ø 900 -
1600mm, Rollerbock 800 - 1800 mm, Taper
Attachment

OPTIONAL ACCESSORY

» Quick change tool holder set Gr. D Multifix quick-
change steel holder set Gr. D