

## heavy duty lahe DKM 2400

Universaldrehmaschine for big turning diameter with a diameter of spindlehole of 130 mm. Theses machinesmodell allows by been 49 KW DC drive motor, the hydraulic clutches- and Brakesystem, such as the bed width of 1100 mm the processing of big Workpieces with high Spatstart fromnahme. Es are turning diameter of until to 3.500mm possible.

### Price upon inquiry

#### specifications

height of center	1200 mm
distance between center	8000 mm
bed width	1100 mm
Swing- $\emptyset$ over bed	2400 mm
Swing- $\emptyset$ over support	2030 mm
diameter of spindlehole	140 mm
speed range	2,5 - 250 U/min
spindlenose	A2-15
range longitudinal feeds	(97) 0,032 - 12 m/U
range cross feeds	(97) 0,016 - 6 m/U
metric thread	(45) 1 - 120 mm
inch thread	(42) 1/4 - 30 Gatg/Inch
model thread	(46) 0,5 - 60 mm
diametral pitch	(48) 0,5 - 60 DP
quill diameter	240 mm
quill stroke	300 mm
quill konus	80/ 1 to 7
power of engine	22 KW/ AC
weight	41.000,00 kg
dimensions	12920 x 2480 x 2610 mm

#### accessoires

4-jaw independent chuck 2000 mm, steady rest  $\emptyset$  220-630 mm, following rest  $\emptyset$  50-220mm, cooling device, Quick feed for Apron, electric driven Tailstock optional: steady rest  $\emptyset$  900 - 1600mm, Rollerbock 800 - 1800 mm, Taper Attachment

#### optinalit accessory

Multifix quick-change steel holder set Gr. D	1.098,00 €
--	------------