

BKM 5032



BKM 5032

SPECIFICATIONS

drilling capacity in steel	32 mm
table size	500x420 mm
Tapping performance steel	M20
clamping surface table	420x340 mm
clamping surface base	370x370 mm
spindle speeds	12 steps 125 - 3030 U/min
distance spindle nose - base	1120 mm
spindle adapter	morse cone 4
quill stroke	155 mm
automatic feeds	0,1/0,2/0,3 mm/U
T-slot table	14 mm
T-slot base	14 mm
distance spindle nose - column	320 mm
diameter of column	120 mm
power of engine	1,0/1,2 KW/400 Volt
weight	460,00 kg
dimensions	900x600x2100 mm

EQUIPMENT

- » machine foot to clamping of high Workpieces
- » 2-stager Motor with 12 shiftable speeds
- » drilling table with t-slots
- » easy and fast speed changes by gear shift
- » gear head 180° swivel-mounted
- » highest smooth running by hardened, ground in oil running gears
- » threading attachment
- » electromagnetic clutch for boring quill feed



ACCESSOIRES

Inkl. threading attachment, cooling pump, Halogen working lamp and autofeed

OPTIONAL ACCESSORY

- » drilling accessories keyless drill chuck B18 3-16mm
- » vices machine vice TQ 140