

BKM 5040L



DRILLING MACHINE

BKM 5040L

SPECIFICATIONS

drilling capacity in steel	40 mm in ST 45
Tapping performance steel	M24
table size	560 x 560 mm
clamping surface table	430x420 mm
clamping surface base	380x470 mm
spindle speeds	50 - 1450 U/min in 18 steps
automatic feeds	0.1/0.2 mm/U
spindle adapter	morse cone 4
quill stroke	180 mm
distance spindle nose - column	350 mm
diameter of column	150 mm
T-slot table	18 mm
T-slot base	18 mm
distance spindle nose - base	1215 mm
power of engine	0,85/1,5 KW 400 Volt
weight	700,00 kg
dimensions	2300x 640x 1150 mm

EQUIPMENT

- » machine foot to clamping of high Workpieces
- » 2-stager Motor with 18 shiftable speeds
- » drilling table with 18 mm t-slots
- » easy and fast speed changes by gear shift
- » hardened, ground in oil running gears
- » threading attachment
- » electronical clutch for boring quill feed



ACCESSORIES

cooling device, mechanical quill feed.

OPTIONAL ACCESSORY

- » drilling accessories keyless drill chuck B16, 1-13mm
- » drilling accessories keyless drill chuck B18 3-16mm
- » other tools reduction sleeve MK4 - B18
- » other tools reduction sleeve MK4 - B16
- » other tools reduction sleeve MK4 - MK3
- ...