

# BKM 3032



**WORKBENCH DRILLPRESS**

# BKM 3032

## SPECIFICATIONS

|  |                          |
|--|--------------------------|
| <b>drilling capacity in steel</b>              | 30 mm                    |
| <b>thread in steel</b>                         | M 24                     |
| <b>working area (LxB)</b>                      | 380x400 mm               |
| <b>speeds</b>                                  | 180-1620 U/min (8 steps) |
| <b>spindle adapter</b>                         | morse cone 3             |
| <b>quill stroke</b>                            | 150 mm                   |
| <b>distance spindle nose - column</b>          | 265 mm                   |
| <b>max. distance spindlenose base</b>          | 750 mm                   |
| <b>Max. distance spindle nose - work table</b> | 390 mm                   |
| <b>diameter of column</b>                      | 100 mm                   |
| <b>power of engine</b>                         | 1,5 KW 400 Volt          |
| <b>weight</b>                                  | 225,00 kg                |
| <b>dimensions</b>                              | 470x640x1390 mm          |

## EQUIPMENT

- » very stable cast iron construction
- » height-adjustable Head body
- » 8 speedsteps
- » machine foot with t-slots and circumferential coolant gutter
- » Taping



## ACCESSORIES

drill chuck adapter, drill chuck, Taping, no base