

benchlathe DKM 250L-1/230V

tabledrehbank with leistungsheavilyem 0,75 KW Motor, gearbox and big distance between center. ground gears in in Oil running for start fromsolut low-noise run.

Highlights

- heightre resolution the Achsspindeln for exactit Positionieren
- complete Electric in Germany by us mounted
- strengthrer Motor with 0,75 KW
- Lenze Frequentoformer

Price upon inquiry

specifications

| | |
|----------------------------|---------------------------|
| height of center | 125 mm |
| distance between center | 700 mm |
| Longitudinal feed | 0,05 - 0,2 mm |
| max. swing over bed | 250 mm |
| max. swing over slider | 130 mm |
| diameter of spindlehole | 27 mm |
| speed range | 115-1620 U/min in 6 steps |
| metric thread | 0,2 - 3,5 mm (20 steps) |
| inch thread | 8 - 56 TPI (20 steps) |
| model thread | 0,2 - 1,25 (10 steps) |
| swivel range of top slider | +/-45° |
| longitudinal movement | 700 mm |
| travel cross | 120 mm |
| quill konus | morse cone 2 |
| quill stroke | 40 mm |
| power of engine | 0,75KW/230 Volt |
| weight | 168,00 kg |
| dimensions | 1410 x 605 x 405 mm |

equipment

- 3 axis digital measurement system with Digital Readout
- produced according DIN 8606
- 27 mm spindle bore
- adjustable guideways "by adjustable ledges"
- hardened and ground gears for low-noise run

accessoires

3-jaw chuck 120mm, change gear set, splash guard

optinalit accessory

| | |
|---|-------------------|
| clamping tool set Multifix Gr. A | 389,00 € |
| 2 mm with insert system 9- pieces | 75,00 € |
| MK2 running | 27,00 € |
| keyless drill chuck B16, 1-13mm | 19,00 € |
| keyless drill chuck B18 3-16mm | Preis auf Anfrage |
| reduction sleeve MK2 - B16 | Preis auf Anfrage |
| reduction sleeve MK2 - B12 | Preis auf Anfrage |
| 0 mm with insert system 7- pieces | 72,00 € |
| 4-B lathe chuck D=125, DIN6350, cast iron | 202,70 € |
| keyless drill chuck B18 1-16mm | 25,00 € |
| 3-B precision lathe chuck D=125, DIN6350, cast iron | 108,50 € |
| turret head set for lathes | 249,50 € |
| 3-B precision lathe chuck Ø=125 with MK 2 Schaft | Preis auf Anfrage |