

DKM 250L-1



DKM 250L-1

SPECIFICATIONS

height of center	125 mm
distance between center	700 mm
Longitudinal feed	0,05 - 0,2 mm
bed width	125mm
max. swing over bed	250 mm
max. swing over slider	130 mm
diameter of spindlehole	27 mm
speed range	115-1620 U/min in 6 steps
metric thread	0,2 - 3,5 mm (20 steps)
inch thread	8 - 56 TPI (20 steps)
model thread	0,2 - 1,25 (10 steps)
swivel range of top slider	+ -45°
longitudinal movement	700 mm
travel cross	114 mm
quill konus	morse cone 2
quill stroke	40 mm
power of engine	0,75KW/400 Volt
weight	152,00 kg
dimensions	1410 x 605 x 405 mm

EQUIPMENT

- » 3-axis digital measurement system with Digital Readout
- » produced according DIN 8606
- » 27 mm spindle bore
- » adjustable guideways "by adjustable ledges"
- » hardened and ground gears for low-noise run



ACCESSORIES

3-jaw chuck 100mm, change gear set, splash guard 3 axis digital measurement system ready mounted .

OPTIONAL ACCESSORY

- » Quick change tool holder set Gr. A clamping tool set Multifix Gr. A
- » clamped turning tool set 1 2 mm with insert system 9- pieces
- » live center MK2 running
- » drilling accessories keyless drill chuck B16, 1-13mm
- ...