

benchlathe DKM 250L-1

tabledrehbank with leistungsheavilyem 750 W Motor, gearbox and big distance between center.ground gears in in Oil running for start fromsolut low-noise run.Ausgittattet with a 3-axis digital Measuring system

Price upon inquiry

specifications

height of center	125 mm
distance between center	700 mm
Longitudinal feed	0,05 - 0,2 mm
bed width	125mm
max. swing over bed	250 mm
max. swing over slider	130 mm
diameter of spindlehole	27 mm
speed range	115-1620 U/min in 6 steps
metric thread	0,2 - 3,5 mm (20 steps)
inch thread	8 - 56 TPI (20 steps)
model thread	0,2 - 1,25 (10 steps)
swivel range of top slider	+45°
longitudinal movement	700 mm
travel cross	114 mm
quill konus	morse cone 2
quill stroke	40 mm
power of engine	0,75KW/400 Volt
weight	152,00 kg
dimensions	1410 x 605 x 405 mm

equipment

- 3-axis digital measurement system with Digital Readout
- produced according DIN 8606
- 27 mm spindle bore
- adjustable guideways "by adjustable ledges"
- hardened and ground gears for low-noise run

accessoires

3-jaw chuck 100mm, change gear set, splash guard 3 axis digital measurement system ready mounted .

optinalit accessory

clamping tool set Multifix Gr. A	389,00 €
2 mm with insert system 9- pieces	75,00 €
MK2 running	27,00 €
keyless drill chuck B16, 1-13mm	19,00 €
keyless drill chuck B18 3-16mm	Preis auf Anfrage
reduction sleeve MK2 - B16	Preis auf Anfrage
0 mm with insert system 7- pieces	72,00 €
4-B lathe chuck D=125, DIN6350, cast iron	202,70 €
keyless drill chuck B18 1-16mm	25,00 €
3-B precision lathe chuck D=125, DIN6350, cast iron	108,50 €
turret head set for lathes	249,50 €