

# DKM 250L/230V



## HIGHLIGHTS

- » high resolution the Achsspindeln for exact Positionieren
- » complete Electric in Germany by us mounted
- » stronger Motor with 0,75 KW
- » Lenze Frequenformer

# DKM 250L/230V

## SPECIFICATIONS

<b>height of center</b>	125 mm
<b>distance between center</b>	700 mm
<b>Longitudinal feed</b>	0,05 - 0,2 mm
<b>bed width</b>	125 mm
<b>max. swing over bed</b>	250 mm
<b>max. swing over slider</b>	130 mm
<b>diameter of spindlehole</b>	27 mm
<b>speed range</b>	115-1620 U/min in 6 steps
<b>metric thread</b>	0,2 - 3,5 mm (20 steps)
<b>inch thread</b>	8 - 56 TPI (20 steps)
<b>model thread</b>	0,2 - 1,25 (10 steps)
<b>swivel range of top slider</b>	+ -45°
<b>longitudinal movement</b>	700 mm
<b>travel cross</b>	120 mm
<b>quill konus</b>	morse cone 2
<b>quill stroke</b>	40 mm
<b>power of engine</b>	0,75KW/230 Volt
<b>weight</b>	168,00 kg
<b>dimensions</b>	1410 x 605 x 405 mm

## EQUIPMENT

- » produced according DIN 8606
- » 27 mm spindle bore
- » adjustable guideways "by adjustable ledges"
- » hardened and ground gears for low-noise run



## ACCESSOIRES

3-jaw chuck 120mm, change gear set, splash guard

## OPTIONAL ACCESSORY

- » live center MK2 running
- » clamped turning tool set 10 mm with insert system 7- pieces
- » drilling accessories keyless drill chuck B18 1-16mm
- » digital readout Lathe 3 - axis digital readout for lathes